



Yantai Lonreytek Technology Co. Ltd

Web: www.lonreytek.com
Email: Info@lonreytek.com
Tel: 0086 0535-2343399
Address: No.2512-2 No.25 Haigang Road Zhifu District
Yantai City Shandong Province China
Zip 264001


All for Your Easy Daily Life& Business

Company Profile

The original demand for end user and AIOT market business mode are rapidly changing in new era.

In respect of smart home, Lonre^ytek manufactures cost-effective and stable smart products based on IOT Cloud Platform, penetrating into thousands of households. Since its establishment, Lonre^ytek has been committed to developing various smart home products and providing personalized services to customers.

In respect of AI and video big data, Lonre^ytek has been cultivating the territory of IoT Industry with its large datasets and partners, launching a number of artificial intelligence advanced technologies and products such as face recognition, human detection, object recognition, etc, which are successfully applied to multiple scenarios and served numerous enterprise customers



GLOBAL SERVICE
AI LEADER
IOT DEVELOPER
ORIGINAL FACTORY

01


Providing excellent product and technology

Smart Security

Smart Camera
Smart Pet Guard
Smart Lock


SMART CAMERA

Smart WiFi PTZ Indoor Camera
Model No.: LTK-SC-I-JP161





Features


- 1080P Full HD video quality, live stream, and watch recordings
- Wide viewing angle, see more of every moment
- Intelligent Auto- Tracking
- 2.4GHz WiFi wireless connection, no network cord required
- Support local storage by MicroSD card up to 128GB
- Support 2-way audio between phone and camera
- Support 7X24H video recordings, never miss every moment
- Free APP provided, support remote viewing on iOS or Android
- Support Tuya cloud storage for motion detected recordings
- Powering by universal power adapter (Micro USB Port, DC5V/1A)
- Flexible installation by wall screws



3MP



WIFI
Connection



Motion
Detect



120°
Viewing
Angle



Night
Vision



Audio


Micro
SD


Cloud
Storage


7X24H


P2P
technology


355°
Design

Accessories

- Smart Camera x 1PC
- Power Adapter (DC5V/1A) x 1PC
- Wall Screws x 1Set
- Quick Start Guide x 1PC


Model	LTK-SC-I-JP161(Smart WiFi PTZ Indoor Camera)
Type	High definition lens
Image Sensor	1/2.7" Color CMOS
Display Resolution	3MP 16： 9
Focal Length	2.8mm
IR Distance	20 meters
Image Frame Rate	15fps(3MP)
Wide dynamic range	Digital wide dynamic
Audio Compression	PCM
WIFI	802.11b/g/n
Reset	Reset button is available
Motion Detection	Support
Working Temperature	-25°C~50°C
Wall Mount Sets	Yes




3MP Smart WiFi PTZ Dome Camera Colorful Night Vision
Model No: LTK-SC-O-JK268

Features

- Clear video quality, live stream, and watch recordings
- Support Intelligent Auto- Tracking
- Rotation angle: Pan:310° Tilt:140°
- Wide viewing angle, see more of every moment
- 2.4GHz WiFi wireless connection, no network cord required
- Support local storage by MicroSD card up to 128GB
- Support 2-way audio between phone and camera
- Support 7X24H video recordings, never miss every moment
- Free APP provided, support remote viewing on iOS or Android
- Support Tuya cloud storage for motion detected recordings
- Powering by universal power adapter (DC12V/1A)
- Flexible installation by wall screws




3MP




WIFI
Connection



Motion
Detect



Viewing
Angle




Night
Vision




Audio




Micro
SD



Cloud
Storage



7X24H



P2P
technology

Accessories

- Smart Camera x 1PC
- Wall Screws x 1Set
- Quick Start Guide x 1PC

Model	LTK-SC-O-JK268
Image Sensor	1/3 CMOS
Display Resolution	3MP 16: 9
Lens Type	High definition lens
Focal Length	2.8mm
IR Distance	20 meters
Image Compression	H.264
Resolution	3MP(2304x1296), 640 x 480(VGA)
Input/Output	Built-in Mic & Speaker
Wireless Security	WEP, WPA, WPA2
Day night mode	Auto change with IR-CUT removable
Cloud	Support cloud storage for TUYA
Working Humidity	20% ~ 95% non-condensing
Wall Mount Sets	Yes

SMART CAMERA

Smart WiFi Cube Indoor Camera
Model No: LTK-SC-I-JK258



Features

- 1080P Full HD video quality, live stream, and watch recordings
- Advanced motion detecting distance up to 5M.
- Wide viewing angle, see more of every moment
- WiFi wireless connection
- Support local storage by MicroSD card up to 128GB
- Support 2-way audio between phone and camera
- Up and down foldable design to make it more compact
- Support 7X24H video recordings, never miss every moment
- Free APP provided, support remote viewing on iOS or Android
- Cloud Storage for motion detected recordings(optional)
- Powering by universal power adapter (Micro USB Port, DC5V/1A)

Accessories

- Smart Camera x 1PC
- Power Adapter (DC5V/1A) x 1PC
- Wall Screws x 1Set
- Quick Start Guide x 1PC



3MP



WiFi
Connection



Motion
Detect



120°
Viewing
Angle



Night
Vision



Audio



Micro
SD



Cloud
Storage



7X24H



P2P
technology

Model	LTK-SC-I-JK258 (Smart WiFi Cube Indoor Camera)
Sensor Type	1/2.7" CMOS
Pixel	2.0MP 1080P(1920*1080)
Lens Type	High definition lens
Viewing Angle	135° (D)/85°(H)
Lens	3.6mm
Infrared Light	6pcs Infrared Light
Image Frame Rate	15fps(1080P)
Input/Output	Built-in Mic & Speaker
WiFi Configuration	SmartConfig
Indicator Light	Blue
Micro SD Card(TF Card)	Maximum support 128GB
Cloud	Support(optional)
Storage Temperature	-10°C ~ 60°C




SMART CAMERA


Smart WiFi Outdoor Camera
Model No.: LTK-SC-O-JK233

Features

- Full HD 3MP video quality, live stream, and watch recordings
- Wide viewing angle, see more of every moment
- 2.4GHz WiFi wireless connection, no network cord required
- Support local storage by MicroSD card up to 128GB
- Support 2-way audio between phone and camera
- Support 7X24H video recordings, never miss every moment
- Free APP provided, support remote viewing on iOS or Android
- Support Tuya cloud storage for motion detected recordings
- Powering by universal power adapter (DC12V/1A)
- Flexible installation by wall screws
- IP65 Waterproof




3MP




WiFi Connection



Motion Detect




Viewing Angle



Night Vision




Audio



Micro SD



Cloud Storage



7X24H



P2P technology

Accessories

- Smart Camera x 1PC
- Wall Screws x 1Set
- Installation bracket x 1PC
- Quick Start Guide x 1PC
- 12V 1A power dapter x 1PC

Model	LTK-SC-O-JK233
Image Sensor	1/3 CMOS
Display Resolution	3MP (2304*1296P)
Lens Type	High definition lens
Focal Length	2.8mm
LED	18pcs IR LED
Day night mode	Auto change with IR-CUT removable
Image Compression	H.264
Input/Output	Built-in Mic & Speaker
WIFI	802.11b/g/n
Wireless Security	WEP, WPA, WPA2
Reset	Reset button is available
Cloud	Support cloud storage for TUYA
Wall Mount Sets	Yes

PET FEEDER

Give pets better care



TUYA Version Smart Pet Feeder With Camera

Model No: LTK-SA-SPF-2200-V

- Remot Control**

 - Smartphone programmable
- Two-way Audio**

 - Talk to your pet via APP
- Health Management**

 - Record pets daily diet and track pets' health
- Accurate Feeding**


 - Schedule up to 10 feeds per day
- 1080P HD Camera**


 - Real-time interaction
- Alarm Function**


 - Notifiations will send to your mobile phone
- Manual Feeding**


 - Dual feeing mode, arbitrary selection
- Dual-power Supply**


 - Backup batteries to maintain normal work


- TUYA


WIFI


1080P


Two-way Audio

Cloud Service
- Feeding Schedule

Automatic & maunal Feeding

5L

Health Management

Sharing

Feeding	Capacity	5 Litres
	Food Type	Dry food only. Do not use canned food. Do not use moist dog or cat food. Do not use treats. Do not use powdery food.
	Feeding Schedule	1-10 meals/day
Audio	Input	Microphone 10meters, -30DBV/Pa
	Output	speaker , 80hm 1w
Camera/Image	Image sensor	1920 x 1080
	View Angle	160
Remote Control	Wi-Fi	IEEE 802.11 b/g/n
	Phone View	Android & IOS
General	Power	USB Adaptor DC 5V 1.0A
	Backup Battery	3 x D cell batteries (no included) 1 x 18650 type Li-ion battery (battery box needed,no included)
	Material	ABS Plastic
	Dimensions	383mm x221mm x338mm (L x W x H)
	Net Weight	1.55 kg

SERIES T: TUYA SMART PET FEEDER

Model: LTK-SA-SPF-2200-WB



Features

- Wi-Fi remote control – Tuya APP Smartphone programmable.
- Bluetooth connection supporting
- Voice control–Google home
- Smart alert: low battery indicator, shortage and food jam alert
- Dual power protective
- Accurate feeding – 1–20 feeds per day, dispense portion from 1 to 15 cups.
- 5L food capacity – see food status through top cover directly.
- Dual power protective – Using 3 x D cell batteries or 1X18650 Li-ion Battery, with Micro USB power cord.

Model	LTK-SA-SPF-2200-WB
Type	Wi-Fi remote Control - Tuya APP
Hopper Capacity	5L
Auto Feeding Time	1-20 meals per day
Microphone	N/A
Speaker	N/A
Battery	3 x D cell batteries+ 1X 18650 Li-ion Battery+USB
Dimension	383*221*338 mm
N. W.	1.55 kgs
Color	White
20GP' FCL	1040 pcs

SMART LOCK

Wisdom protects thousands of families
and opens a convenient life

TUYA Version Smart Pet Feeder With Camera

Model No:A230-BN

- Smart Bluetooth Digital Lock,
- Work with proximity card
- 304# stainless steel handle
- Zinc alloy panel
- Black nickel treatment
- Single latch or 50/50 mortise
- Work with alkaline battery
- Emergency key for backup use
- 300,000 times life test
- Work with bluetooth technology
- Support remote passcode change
- No need front reception and save labor cost
- Available for WIFI hub for remote management(optional)



SMART BLE DIGITAL FINGERPRINT LOCK,

Model No.:LTK-SL-LF-260

Single latch
5050/6050
5572Mortise



01

Smart key Box K3

LTK-SL-LF-260
app unlock
unlock record



02

Smart Bluetooth Glass Lock

LTK-SL-AK-M500
Single Carton:
195x75x190mm



03

Smart Bluetooth Glass Lock

LTK-SL-LF-A09
Single Carton:
195x75x190mm



04

Smart Bluetooth Glass Lock

12pcs/carton
Single Carton:
195x75x190mm

Providing excellent product and technology

Smart Sensors

L Series

J Series



L SERIES

precision detection



ZigBee USB PIR Motion Sensor

LTK-SS-W-Z-PIR-L02

Function description

- Battery: CR123A*2-3V
- USB Power supply: 5V/1A
- Sensitive distance: 12m
- Sensitive angle: 120°C
- Working Temperature: 0°C~ 40°C (32°F~104°F)
- Working humidity: 20% ~ 85%
- Wireless frequency: 2.4GHz
- Wireless protocol: Zigbee 3.0 IEEE 802.15.4
- Size: 68mm x 56mm x 56mm



ZigBee USB Door Sensor

LTK-SS-W-Z-DS-L02

Function description

- Backup battery: CR123A 3V
- USB Power supply: 5V 1A
- Standby current: 10.7uA
- Working Temperature: 0°C~ 40°C (32°F~104°F)
- Working humidity: 20% ~ 85%
- Wireless frequency: 2.4GHz
- Wireless protocol: Zigbee 3.0, IEEE 802.15.4
- Network range: 55M
- Product size: Main body: 82mm*27mm*23mm
Deputy body: 50mm*13mm*16mm





ZigBee USB Siren Alarm Sensor

LTK-SS-W-Z-SIREN-L02

- Battery: CR123A*2-3V
- USB Power supply: 5V/1A
- Volume: 90db
- Working Temperature: 0°C ~ 40°C (32°F ~ 104°F)
- Working humidity: 20% ~ 85%
- Wireless frequency: 2.4GHz
- Network range: 40M
- Wireless protocol : Zigbee 3.0 IEEE 802.15.4
- Size: 68mm x 68mm x 33mm



ZigBee Water Flood Sensor

LTK-SS-W-Z-WS-L02

- Detect water leakage and push notification to mobile phone
- App remote control
- Battery: CR2-3V
- Standby current: 1.1uA
- Waterproof level: IP55
- Working Temp.: 0°C~40°C
- Working hum.: 20%~85%
- Wireless frequency: 2.4GHz
- Wireless protocol: Zigbee 3.0, IEEE 802.15.4
- Network range: 55M
- Product size: 69mm*69mm*34mm

3 in 1 device(siren humidity and temperature sensor)

LTK-SS-W-Z-TH-L02

- With temperature and humidity sensor
- Detect luminous intensity
- Push notification to mobile phone
- Free IOS & android APP
- Battery: AA battery*2pcs
- Temperature detect range: -20°C ~ 80 °C
- Humidity detect range: 0% ~ 100%
- Luminous intensity detect range: 0Lux ~ 157000Lux
- Working temperature: -20°C ~ 80°C (-4°F ~ 176°F)
- Working humidity: 0% ~ 100%
- Size: 84mm x 55mm x 32mm



Tuya Smart WiFi ZigBee Gateway

LTK-SS-W-W-PIR-L02

- ZigBee control center,
- Supports adding multiple sub-devices.
- USB power supply: 5V 1A
- Working temperature: -10~55
- Working humidity: 10%~90%RU
- Storage temperature: -10~55°C
- Storage humidity: 10%~90%RU
- Wireless protocol: Zigbee 3.0 IEEE 802.15.4
- Network range: 55M
- Firmware upgrade: Support OTA
- Product size: 78mm*78mm*25mm
- Free app: TuyaSmart or Smart Life.
- Support systems: Android and IOS.



J SERIES

precision detection



Tuya Wireless Multi Mode Gateway

LTK-SS-W-Z-Z-GW-J01

Specification

Power input: 5V1A
Working power: <1A
Working temperature: -10°C-55°C
Working humidity: 10%-90% RH (non-condensing)
Wireless technology: 2.4G WIFI & Zigbee & BLE5.0 & Mesh
Size: 60*60*15mm



Tuya Zigbee PIR Motion Sensor

LTK-SS-W-Z-PIR-J01


Specification

Detection distance: 7-10M
Detection angle: wide angle 120°
Battery: 3V CR2450
Working temperature: -10°C-55°C
Working humidity: 10%-90%RH (no condensation)
Main function: intelligent linkage
Wireless standard: WIFI802.11b/g/n
Zigbee802.15.4

01 Tuya WiFi Flood Sensor WiF

LTK-SS-W-Z-PIR-J01

Wireless type: 2.4GHz
Wireless standard: IEEE 802.11b/g/n
Wireless range: 30-45m
Working temperature: 0°C~40°C (32°F~104°F)
Working humidity: 20%~85%
Storage temperature: 0°C to 60°C (32°F to 140°F)
Storage humidity: 0% to 90%



02 Tuya Wifi Garage Door Opener

LTK-SS-B-W-GC-J01

Multi-user access and remote monitoring
2.4GHz WIFI one-key connection for easy setup
Smart linkage with other smart home devices
Home/Away mode automatically turns on/off
Support Amazon alexa and Google home, voice control
Specification:
Power supply mode: 1) DC5V 2) AC100-240V 3) DC9-36V
Wireless standard: IEEE 802.11b/g/n
color: black
Installation method: wall-mounted
Material: ABS

03 Tuya Zigbee Contact Sensor

LTK-SS-W-Z-DS-01

Battery: CR2032
Working temperature: -10°C~55°C
Working humidity: 10%-90%RH (no condensation)
Main function: intelligent linkage
Wireless standard:
Zigbee802.15.4
Shell material: ABS



04 Temperature and humidity sensor

WIFI:LTK-SS-W-W-TH-J01
Zigbee:LTK-SS-W-Z-TH-J01
BLE: LTK-SS-W-B-TH-J01

Intelligent temperature and humidity sensor
Communication method: WIFI/ Zigbee/Bluetooth BLE
Dimensions: 84*80*20mm
Working temperature: -10~+55°C 0~100%RH
Power supply mode: DC 4.5V (3 AAA batteries)
Standby current: 26uA ~ 250uA (dynamic change)
Wireless communication distance: >= 20 meters
Temperature error: typical error +-0.5 degrees Celsius, maximum error +-2.0 degrees Celsius
Relative humidity error: typical error +-5%, maximum error +-8%



05 wifi door sensor

LTK-SS-W-W-DS-J01

Function: detect the open/close state of the door/window
2.4GHz WIFI/BLE one-key connection for easy setup
Standby time up to 6-10 months Low battery reminder
Works with Amazon alexa and Google home,
Specification:
Batteries: AAA 1.5V x 2
Standby current: <5uA
Wireless type: 2.4GHz WIFI
Protocol: IEEE 802.11b/g/n 2.4G wifi
Standby time: 6 - 10 months
Material: ABS
Working temperature: -10°C~40°C (14°F~104°F)
Working humidity: 20% ~ 85%



Providing excellent product and technology

Smart Lighting



Controller
Light
Electronic Spare Parts



RGB+CCT Ground spotlight

- Model :LTK-SL-BL-LMGS01Z
- Input Voltage: DC24V
- Power: 6W
- Lifespan: 50000 hours




Dual White LED Controller

- Model No : LTK-SL-C-C01Z
- Input Voltage: DC5-24V
- Output: 7.5A/Channel



RGB+CCT LED Strip

- Model No : LTK-SL-C-LM051
- 2.4GHz RF Remote Control
- Tuya Smart Life APP WiFi Wireless Control



Model No.: LM080
Zigbee 3.0 GU10 RGB+CCT LED Spotlight

FEATURES

Smartphone APP control, Support third party voice control (Zigbee 3.0 gateway is needed), Work with Philip Hue APP (Philip Hue Bridge is needed). 16 Millions of colors to choose, Color temperature, Dim brightness & Saturation adjustable. Auto-transmitting & Synchronization function make control distance limitless.

- RGB+CCT
16 Millions of colors to choose
- Dim brightness / saturation
- Color temperature
2700K-6500K
- Work with Philip Hue APP
(Philip Hue Bridge is needed)
- Tap-to-Run & automation
- Music Rhythm function
- Biorhythm
- Smart phone APP control
(Tuya Zigbee gateway is needed)
- Timing setting / countdown
turn on / off LED light
- Sleep / wakeup plan
- Do not disturb mode
- Support third party voice control
(Tuya Zigbee gateway is needed)
- Device sharing

Model No.	Power	Input Voltage	Color Temp.	Luminous Flux	Light Efficiency	Rated Current	CRI	Working Temp.	Beam Angle	Lifespan
LM080	4W	AC100-240V 50/60Hz	2700K-6500K	300LM-320LM	80LM/W	0.07A	>80	-10-40°C	30°	50000 hours



Model No.: LM072

12W RGB+CCT LED Downlight

FEATURES

Smartphone APP control, Support third party voice control (2.4GHz gateway is needed). 16 Millions of colors to choose, Color temperature, Dim brightness & Saturation adjustable. Auto-transmitting & Synchronization function make control distance limitless.

- RGB+CCT
16 Millions of colors to choose
- Color temperature
2700K-6500K
- Dim brightness / saturation
- Smart phone APP control
(2.4GHz gateway is needed)
- Signal transmitting & Modes synchronization
- 2.4G RF wireless transmission technology
- Remote control
Control distance 30m
- Support third party voice control
(2.4GHz gateway is needed)

Model No.	Power	Input Voltage	Color Temp.	Luminous Flux	Light Efficiency	CRI	RF	Working Temp.	Beam Angle	Hole Size
LM072	12W	AC100~240V 50/60Hz	2700K~6500K	1100LM	88LM/W	>80	>0.5	-20~60°C	120°	Φ 140~145mm



Model No.: LM091

2.4GHz RF 4-Zone RGB& RGBW&RGBCCT Remote Controller

FEATURES

Adopt world-wide used 2.4GHz frequency, GFSK control method, with the features of low power consumption, long distance transmitting, strong anti-interference and fast communication rate; can change the color, color temperature, saturation and brightness.

- 16 Millions of colors to choose
- Color temperature adjustable
- Brightness Dimming
- 2.4G RF wireless transmission technology
- 4-Channel groups control separately
- Mode saving function



Model No.	Working Voltage	Transmitting Power	Standby Power Consumption	Transmission Frequency	Modulation Method	Working Temperature	Control Distance
LM091	3V(AAA * 2PCS)	6dBm	15uA	2.4GHz	GFSK	-20~60°C	30m


WIFI 2 USB Smart Plug

- LTK-SE-W-W-2U-B01
- Timing function
- Counting function
- Breakdown Memory
- Status Feedback
- Share
- Over load Protection
- Manual Switch
- Group
- Amazon Google
- Ble connecting



Product	2 AC + 2 USB
size	USA
output	16A/AC
voltage	AC100-240V 50/60Hz
color	white
material	PC
Hum	<80%
Tem	-20℃ -+50℃
Wifi distance	50 outdoor , 30indoor
Wifi type	2.4GHZ 802.11b/g/n
Network safety	WPA/WPA2





WIFI CURTAIN MODULE

LTK-SE-W-W-GC-Z01

CREATE SCHEDULE
Automatically turn room curtains on and
off by planning



Wifi 2 Channel Dimmer Module With Neutral

LTK-SE-W-W-2D-Z01



Wifi 2 Channel Switch Module With Neutral And Power Consumption

LTK-SE-W-W-2S-PC-Z01



Wifi 2 Channel Switch Module With Neutral

LTK-SE-W-W-2S-Z01



Wifi 3 Channel Switch Module With Neutral

LTK-SE-W-W-3S-Z01




Wifi 4 Channel Switch Module With Neutral

LTK-SE-W-W-4S-Z01

APP REMOTE CONTROL

Open the mobile app to view, remotely
switch and adjust the room temperature



HELP YOU MOVE
TOWARDS SMART LIFE

EMPOWER YOUR
SMART BUSINESS

